CX1577

15 inch Coaxial Loudspeaker



Overview

The CX1577 is a coaxial loudspeaker that provides the output capability and pattern control of a normal 2-way system in a much more compact enclosure. Its coaxial transducer and 75° x 75° horn provides effective coverage in situations where traditional 45° and 60° vertical patterns are too narrow. Its coverage pattern is particularly effective from an elevated position, and its vertically trapezoidal enclosure shape allows it to be mounted very close to ceilings with minimal effect on sight lines.

Fulcrum Acoustic's **TQ**™ processing is an integral part of the CX1577 design. Sound, innovative acoustical design combined with state of the art digital processing leads to exceptional clarity and precise transient response, even at very high sound pressure levels. The required digital signal processing can be provided by one of many supported platforms.

The CX1577 is particularly effective in systems where targeted pattern control is desirable, and is an excellent solution for high fidelity, foreground distributed systems. Its unique shape and compact size complements many architectural styles, which facilitates acceptance by interior designers and architects. This makes it the perfect choice for houses of worship, theaters, restaurants, transportation facilities, theme parks, and more.

Performance Specifications[1]

Operating Mode
Single-amplified w/ DSP

Operating Range [2]
57 Hz to 20 kHz

Nominal Beamwidth
75° x 75°

Transducers
HF/LF: Coaxial 3.0 inch titanium diaphragm compression driver; 15.0 inch woofer, 3.0 inch voice coil; single neodymium magnet

Power Handling @ Nominal Impedance [3]
57 V / 400 W @ 8 Ω

Nominal Sensitivity @ Input Voltage [4] (whole space)
103 dB @ 2.83 V

Nominal Maximum SPL (peak / continuous)
135 dB / 129 dB

Equalized Sensitivity @ Input Voltage [5]
99 dB @ 2.83 V

Equalized Maximum SPL [6] (peak / continuous)
131 dB / 125 dB

Recommended Power Amplifier
400 W to 800 W @ 8 Ω

Physical Specifications

Connections
(2) Neutrik NL4 Speakon
Pin 1+/-: Full Range
Pin 2+/-: No Connection

Mounting / Suspension Points
(12) M10 x 1.5 eye bolt angle points, (2) M10 x 1.5 yoke points


Dimensions / Weight
See pages 5 & 6

Finish
Black painted enclosure w/ matte black grille, or
White painted enclosure w/ matte white grille


Options

YK-CX15 yoke bracket, Terminal strip input, Custom color finish, Weather-resistant (WR) enclosure & hardware


Axial Sensitivity (dB SPL, 2.83 V @ 1 m) [7, 8]




Horizontal Off Axis Response [7, 11]




Axial Processed Response (dB) [7, 9]




Vertical Off Axis Response [7, 11]




Axial Processed Phase Response (degrees) [7, 10]




Beamwidth [7, 12]




Impedance (ohms)




Directivity Index (dB) [13]



Horizontal Polar Response (30 dB Scale, 6 dB per Major Division)



Vertical Polar Response (30 dB Scale, 6 dB per Major Division)



Technologies


The proprietary horns employed in the CX Series represent a modern digital-signal-processing-aware update to the traditional horn-loaded coaxial loudspeaker concept. The well-known benefits of the coaxial approach have been realized without the familiar shortcomings of historical designs. Fulcrum Acoustic's **Temporal Equalization™ (TQ™)** digital signal processing techniques eliminate midrange colorations and high frequency harshness while producing a smooth, seamless coverage pattern through the crossover range. In fact, the coaxial transducers were designed from the ground up to take advantage of the unique capabilities of **TQ™**.

The coaxial transducer in the CX1577 includes a 3 inch diaphragm compression driver. The large diaphragm area permits the compression driver to operate at frequencies too low for smaller compression drivers to handle. This allows the high frequency horn to smooth the polar response of the low frequency section in the frequency range where the horn would otherwise cause shadowing. It also allows the compression driver to produce extreme sound pressure levels with an effortless sonic character.

The coaxial woofer's large radiating surface works in conjunction with the HF horn to improve directional control at the bottom of the horn's operating range, increasing directional control beyond what can be accomplished by the horn alone. The coaxial transducer's compact, neodymium magnet not only minimizes weight, but also allows very tight spacing between the compression driver and woofer voice coils. The delay between the driver outputs is thereby minimized, which allows the coaxial device to work well with a passive crossover.

Connections

Neutrik NL4 Speakon Input



Mechanical Specification Drawings

2D and 3D DWG dimensional drawings are available for download at www.fulcrum-acoustic.com/resources

Notes

[1] **Performance Specifications** *All acoustic specifications rounded to nearest whole number. External DSP with Fulcrum Acoustic-provided settings is required to achieve the specified performance.*

[2] **Operating Range** *The frequency range within which the processed response is within 10 dB of the average.*

[3] **Power Handling** *Based on the AES power handling of the transducers.*

[4] **Nominal Sensitivity** *The 1-meter-referenced SPL produced by a 1 watt band limited pink noise signal, with no processing applied.*

[5] **Equalized Sensitivity** *The 1-meter-referenced SPL produced when an EIA-426-B signal is applied to an equalized loudspeaker system, at a level which produces a total power of 1 watt, in sum, to the loudspeaker subsections.*

[6] **Equalized Maximum SPL** *The 1-meter-referenced SPL produced when an EIA-426-B signal is applied to an equalized loudspeaker system, at a level which drives at least one subsection to its rated power.*

[7] **Resolution** *All response graphs are subjected to 1/6 octave cepstral smoothing with a gaussian weighting function.*

[8] **Axial Sensitivity** *The SPL plotted against frequency for a 1 watt swept sine wave, referenced to 1 m with no signal processing.*

[9] **Axial Processed Response** *The axial magnitude response with recommended signal processing applied.*

[10] **Axial Processed Phase Response** *The axial phase response with recommended signal processing applied, and latency removed.*

[11] **Horizontal / Vertical Off Axis Responses** *The magnitude response at various angles off axis, with recommended signal proceessing applied.*


[12] **Beamwidth** *The angle between the -6 dB points in a loudspeaker's polar response.*


[13] **Directivity Index (D_i)** *The ratio of the on-axis sound pressure squared to the spherical average of the sound pressure squared at a particular frequency expressed in dB. To convert the directivity index to directivity factor (Q) use the formula* $10^{D_i/10}$.

Notes:
1. Net Weight = Approx. 42.5 lb / 19.3 kg
2. Symbol ⊙ = M10x1.5 eye bolt angle point
3. Symbol ⊙ = M10x1.5 nut plate
4. Symbol ⊕ = CoG
5. Drawing representative of:
   CX1526, CX1565, CX1577, CX1595


REVISIONS


REV	DESCRIPTION	APPR / DATE
6	ADD SHIPPING WEIGHT	RAF 12/7/11
7	OMNIMOUNT TO "THIRD PARTY" IN NOTE 5	RAF 1/13/12
8	CHANGE DRAWING NAME TO "CX15 SERIES"	RAF 5/9/12
9	ADD "CX1526" TO NOTE 7	RAF 6/3/13
10	REMOVE PAN/TILT MOUNT POINTS	RAF 7/28/16
11	UPDATE DIMS, FIX DRAWING ERRORS	RAF 1/18/21
12	UPDATE NOTES, MOVE REAR POINTS	RAF 6/23/25






GRILLE PARTIALLY SHOWN







THIRD ANGLE PROJECTION	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCE IN INCHES .X±.1 .XX±.015 .XXX±.005 FRACTIONS ±1/32 ANGLES ±1/2° (X.XX) = REF DIMS NO TOLERANCE IMPLIED TSC = THEORETICAL SHARP CORNER DIMENSIONS ACROSS CENTERLINES TO BE SYMETRICAL	STATUS RELEASED	FULCRUM ACOUSTIC, LLC 1 MAIN STREET, WHITINSVILLE, MA 01588 USA
		APPROVALS / DATE	TITLE: Mechanical Spec, CX15 Series
		DRAWN: DWG 2/09/09	
		CHECKED: RAF 6/12/09	
		DES ENG:	B SHEET 1 OF 1 SCALE: 1:16
		MFG ENG:	DWG. NO. 820-100-015 REV 12


THIS DRAWING IS THE PROPERTY OF FULCRUM ACOUSTIC, AND SHALL NOT BE COPIED, REPRODUCED, OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF APPARATUS WITHOU WRITTEN AUTHORIZATION.
DO NOT SCALE DRAWING.


Drawing is reduced. Do not scale.

Notes:
1. Net Weight <= Approx. 42.5 lb / 19.3 kg
2. Symbol ⊙ = M10x1.5 eye bolt angle point
3. Symbol ⊙ = M10x1.5 nut plate
4. Symbol ⊕ = CoG
5. Enclosure construction:
   Fiberglass Reinforced Polyurethane
6. Drawing representative of:
   CX1526-WR, CX1565-WR, CX1577-WR, CX1595-WR


REVISIONS


REV	DESCRIPTION	APPR / DATE
1	NEW ISSUE	RAF 1/11/16
2	REMOVE PAN/TILT MOUNT POINTS	RAF 7/28/16
3	REDRAWN FOR FRP	DEW 4/3/18
4	MOVE INPUT, CHANGE COVER PLATE, UPDATE DIMENSIONS	RAF 1/14/21
5	UPDATE NOTES, INPUT COVER PLATE	RAF 6/25/25






GRILLE PARTIALLY SHOWN








THIRD ANGLE PROJECTION	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCE IN INCHES .X±.1 .XX±.015 .XXX±.005 FRACTIONS ±1/32 ANGLES ±1/2° (X.XX) = REF DIMS NO TOLERANCE IMPLIED TSC = THEORETICAL SHARP CORNER DIMENSIONS ACROSS CENTERLINES TO BE SYMETRICAL	STATUS RELEASED	FULCRUM ACOUSTIC, LLC 1 MAIN STREET, WHITINSVILLE, MA 01588 USA
		APPROVALS / DATE	TITLE: Mechanical Spec, CX15 Series - WR
		DRAWN: RAF 1/11/16	
		CHECKED: DWG 1/11/16	
		DES ENG:	B SHEET 1 OF 1 SCALE: 1:16
THIS DRAWING IS THE PROPERTY OF FULCRUM ACOUSTIC, AND SHALL NOT BE COPIED, REPRODUCED, OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF APPARATUS WITHOU WRITTEN AUTHORIZATION. DO NOT SCALE DRAWING.		MFG ENG:	DWG. NO. 820-100-088 REV 5

Drawing is reduced. Do not scale.

Notes:
1. Fits: CX15 Series & CCX15 Series
2. Net Weight: Approx. 9.6 lb / 4.4 kg
3. Material: 8 GA ASTM A36 steel
4. Includes 2x each M10 socket head cap screws, split washers, and flat washers

REVISIONS		
REV	DESCRIPTION	APPR / DATE
1	NEW ISSUE	06/29/20
2	UPDATE NOTES & WASHER QTY	01/14/21
3	ADD CCX15 REF TO NOTES	06/30/22
4	UPDATE WASHERS	06/24/25




THIRD ANGLE PROJECTION	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCE IN INCHES .X±.1 .XX±.015 .XXX±.005 FRACTIONS ±1/32 ANGLES ±1/2° (X.XX) = REF DIMS NO TOLERANCE IMPLIED TSC = THEORETICAL SHARP CORNER DIMENSIONS ACROSS CENTERLINES TO BE SYMETRICAL	STATUS RELEASED	FULCRUM ACOUSTIC, LLC 1 MAIN STREET, WHITINSVILLE, MA 01588 USA
THIS DRAWING IS THE PROPERTY OF FULCRUM ACOUSTIC, AND SHALL NOT BE COPIED, REPRODUCED, OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF APPARATUS WITHOU WRITTEN AUTHORIZATION. DO NOT SCALE DRAWING.		APPROVALS / DATE DRAWN: RAF 06/29/20 CHECKED: DWG 06/30/20 DES ENG: MFG ENG:	TITLE: Mechanical Spec, YK-CX15 Yoke Bracket A SHEET 1 OF 1 SCALE: 1:6 DWG. NO. 820-300-036 REV 4

Drawing is reduced. Do not scale.


Notes:
The YK-CX15 yoke bracket is designed to mount CX15 & CCX15 Series loudspeakers in a horizontal orientation. It is fitted with two mounting holes which allow the installer to vary the distance between the loudspeaker enclosure and the mounting surface.

Note that the range of motion is restricted when the enclosure is mounted closer to the yoke. The maximum range of motion is achieved when the enclosure is mounted to the holes nearest the end of the bracket arms.


REVISIONS		
REV	DESCRIPTION	APPR / DATE
1	NEW ISSUE	RAF 06/29/20
2	ADD CCX15 REF TO NOTES	RAF 06/30/22
3	CHANGE DRAWING ORIENTATION	RAF 06/24/25




MOUNTING POSTION 1



MOUNTING POSTION 2





THIRD ANGLE PROJECTION	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCE IN INCHES .X±.1 .XX±.015 .XXX±.005 FRACTIONS ±1/32 ANGLES ±1/2° (X.XX) = REF DIMS NO TOLERANCE IMPLIED TSC = THEORETICAL SHARP CORNER DIMENSIONS ACROSS CENTERLINES TO BE SYMETRICAL	STATUS RELEASED	FULCRUM ACOUSTIC, LLC 1 MAIN STREET, WHITINSVILLE, MA 01588 USA
		APPROVALS / DATE	
		DRAWN: RAF 06/29/20	TITLE: Mechanical Spec, YK-CX15 + CX15xx Assembly
		CHECKED: DWG 06/30/20	
		DES ENG:	A SHEET 1 OF 1 SCALE: 1:12
THIS DRAWING IS THE PROPERTY OF FULCRUM ACOUSTIC, AND SHALL NOT BE COPIED, REPRODUCED, OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF APPARATUS WITHOU WRITTEN AUTHORIZATION. DO NOT SCALE DRAWING.		MFG ENG:	DWG. NO. 820-300-037 REV 3

Drawing is reduced. Do not scale.